



Total Quality. Assured.

545 E Algonquin Road, Suite H  
Arlington Heights, IL 60005 USA

Telephone: 847-439-5667  
[intertek.com](http://intertek.com)

Published:  
Revised:

2-Dec-20

Public Notice ID: 2020-34  
Page 1 of 2

## Counterfeit Intertek Certified Product Notification / Notification de produit certifié Intertek contrefaite Luminaire - FHS4NCLED

Notification Type:	Counterfeiting / Contrefaçon
Certification Type:	Not Intertek Certified

### Notification

Intertek notifies consumers, retailers and distributors of a potential safety concern involving the Intertek Certified products identified below. / Intertek informe les consommateurs, les détaillants et les distributeurs d'une préoccupation potentielle en matière de sécurité impliquant les produits certifiés Intertek identifiés ci-dessous.

### Company Identification

Unknown

### Product Identification

The following counterfeit product, Luminaire model FHS4NCLED with cETLus counterfeit Control Number 3193488. Photos are located on Page 2.

### Hazard Involved

Unknown

### What To Do

Use of these products should be immediately discontinued and return to the point of purchase. Distributors and retailers should discontinue sales and return inventories to their suppliers. / L'utilisation de ces produits doit être immédiatement abandonnée et retourner au point d'achat. Les distributeurs et les détaillants doivent cesser les ventes et retourner les inventaires à leurs fournisseurs.



Total Quality. Assured.


545 E Algonquin Road, Suite H  
Arlington Heights, IL 60005 USA

Telephone: 847-439-5667  
**intertek.com**

Published: December 2, 2020  
Revised:

Public Notice ID: 2020-34  
Page 2 of 2

**Photos and Images**

WARNING: RISK OF FIRE. USE ONLY SUITABLE TRIMS FOR EACH LAMP AND WATTAGE INDICATED. AVERTISSEMENT: RISQUE DE FEU. UTILISER UNIQUEMENT DES GARNITURE POUR LAMPPE ET PUISSANCE INDIQUEE.		FOR USE ONLY WITH UL OR cUL CLASSIFIED LED RETROFIT KIT SUITABLE FOR 6 INCH RECESSED HOUSING	
		CONFORMS TO UL STANDARD #1598 CERTIFIED TO CSA STANDARD C22.2#250.0	
<b>FHS4NC-LED</b>			
<b>Air Tight</b> THIS AIRTIGHT FIXTURE COMPLIES WITH WASHINGTON STATE ENERGY CODE ASTM-E283 MEASURED AT 2CFM OR LESS	INHERENTLY PROTECTED	ACCESS ABOVE CEILING REQUIRED	LED RECESSED LUMINAIRE FITTING
			LED RECESSED LUMINAIRE FITTING
	TYPE IC APPROVED FOR DIRECT CONTACT WITH INSULATION	 Intertek 3193488	120V 60Hz LED 13W MAX. T24
<b>SUITABLE FOR DAMP LOCATIONS</b>	MAXIMUM OF 6 12 AWG or 8 14 AWG THROUGH BRANCH CIRCUIT CONDUCTOR SUITABLE FOR 70°C PERMITTED IN BOX. MIN 90°C SUPPLY CONDUCTORS FOR CABLE USE ONLY-NOT FOR PULLING WIRES VAPOR BARRIER MUST BE SUITABLE FOR 90 °C		
NOTICE: THERMALLY PROTECTED FIXTURES BLINKING LIGHT MAY INDICATE IMPROPER LAMP SIZE. FOR SUPPLY CONNECTION USE WIRE RATED AT LEAST 90°C			

